

Via Maltese, 62/64 - 90146 Palermo (PA) - Italia Tel. 091 685 1784 Mobile +39 351 8753628

e-mail: info@allfoodproject.com website: www.allfoodproject.com.com

C.F. GLLBGI66L21G273C VAT Number 03765550821 Company Registered Number 162241

Estimate No.

7020

of the

11/20/2024

Info

CALL us for FREE consulting service Tel 091 685 1784 or CHAT with us on Whatsapp +393518753628

Cod. art.	Description	Qty	Price	Discount	Amount

CLOE/IG1

AFP / CLOE sanitizing gel

1

€299.82



- Appearance: Clear gel - Color:

Colorless - Odor:

Characteristic - Relative density: 1kg / I

pH: 8 -

Solubility in water: Total - Can 5 Lt

## **Technical Sheet**

Door opening from right to left  Dimensions cm L 80 x P 81.1 x 50.2 h  Timer provided  Thermostat 48 - 260 C  Capacity: 4 trays (included)  Power 6.9 kw  CE standard  Energy saving mode  Trays distances 7,5 cm  Weight 55 kg  Dry mode: removal of humidity from the cooking chamber  Internal cooking chamber lighting  Gear immersion fans  Control panel: 896 storable programs  From 1 to 3 cooking steps  Humidity in percentage 0-20406080100%		
Timer provided  Capacity: 4 trays (included)  Power 6.9 kw  CE standard  Energy saving mode  Trays distances 7,5 cm  Weight 55 kg  Dry mode: removal of humidity from the cooking chamber  Internal cooking chamber lighting  Gear immersion fans  Control panel: 896 storable programs  From 1 to 3 cooking steps  Humidity in percentage 0-20406080100%  Touch screen control panel with LCD display  Al technology: learns from previous cooking and regulate	Structure: stainless steel	Power supply
Capacity: 4 trays (included)  CE standard  Energy saving mode  Trays distances 7,5 cm  Weight 55 kg  Dry mode: removal of humidity from the cooking chamber  Internal cooking chamber lighting  Gear immersion fans  Control panel: 896 storable programs  From 1 to 3 cooking steps  Humidity in percentage 0-20406080100%  Touch screen control panel with LCD display  Al technology: learns from previous cooking and regulate	Door opening from right to left	Dimensions cm L 80 x P 81.1 x 50.2 h
CE standard Energy saving mode  Trays distances 7,5 cm Weight 55 kg  Dry mode: removal of humidity from the cooking chamber Safety temperature limiter  Internal cooking chamber lighting Double glazing  Gear immersion fans Control panel: 896 storable programs  From 1 to 3 cooking steps Humidity in percentage 0-20406080100%  Touch screen control panel with LCD display AI technology: learns from previous cooking and regulate	Timer provided	Thermostat 48 - 260 C
Trays distances 7,5 cm  Weight 55 kg  Dry mode: removal of humidity from the cooking chamber Internal cooking chamber lighting  Gear immersion fans  Control panel: 896 storable programs  From 1 to 3 cooking steps  Humidity in percentage 0-20406080100%  Touch screen control panel with LCD display  Al technology: learns from previous cooking and regulate	Capacity: 4 trays (included)	Power 6.9 kw
Dry mode: removal of humidity from the cooking chamber Internal cooking chamber lighting Gear immersion fans Control panel: 896 storable programs From 1 to 3 cooking steps Humidity in percentage 0-20406080100% Touch screen control panel with LCD display Al technology: learns from previous cooking and regulate	CE standard	Energy saving mode
Internal cooking chamber lighting  Gear immersion fans  Control panel: 896 storable programs  From 1 to 3 cooking steps  Humidity in percentage 0-20406080100%  Touch screen control panel with LCD display  Al technology: learns from previous cooking and regulate	Trays distances 7,5 cm	Weight 55 kg
Gear immersion fans  Control panel: 896 storable programs  From 1 to 3 cooking steps  Humidity in percentage 0-20406080100%  Touch screen control panel with LCD display  Al technology: learns from previous cooking and regulate	Dry mode: removal of humidity from the cooking chamber	Safety temperature limiter
From 1 to 3 cooking steps  Humidity in percentage 0-20406080100%  Touch screen control panel with LCD display  Al technology: learns from previous cooking and regulate	Internal cooking chamber lighting	Double glazing
Touch screen control panel with LCD display  Al technology: learns from previous cooking and regulate	Gear immersion fans	Control panel: 896 storable programs
	From 1 to 3 cooking steps	Humidity in percentage 0-20406080100%
	Touch screen control panel with LCD display	Al technology: learns from previous cooking and regulates the pre-heating temperature for the next program.



+ Add Product





For countries outside of Italy, shipping costs may vary. We will send you a quotation after receiving this order confirmation.

Pursuant to Legislative Decree 196/2003 we only use your data for the purpose of communicating with existing commercial relations between us.

Please check your personal data, VAT number and Tax Code. We are not responsible for any errors.